

# WHOLE HOUSE CARBON FILTRATION SYSTEMS





## **APPLICATIONS**

Whole House

## **FEATURES • BENEFITS**

- Simple, electronic system for easy programming; maintains settings during power outages
- Automatic bypass for uninterrupted water flow to the home during regeneration
- Singular, rotary disc seal means longer life and lower maintenance
- Coconut shell-based carbon for highly effective chlorine reduction and long life
- 1.0, 1.5 and 2.0 cubic foot capacities available to meet household demand requirements

### **SPECIFICATIONS**

PART NO.	35923	35924	35925
Rated Service Flow (gpm)	11.6	11.9	13.2
Pressure Drop at Rated Service Flow Rate (psi)	12	15	15
Carbon Filtration Media (cu ft)	1.0	1.5	2.0
Tank Size (dia x h)	10" x 44"	10" x 54"	12" x 48"

### **VALVE SPECIFICATIONS**

Valve Body Glass-Filled Thermoplastic

Rubber Components Compounded For Cold Water

Operating Pressure 20 - 120 psi (1.38 - 8.27 bar)

Water Temperature  $40^{\circ} - 100^{\circ} F (4.4^{\circ} - 38^{\circ} C)$ 

Ambient Temperature  $40^{\circ} - 100^{\circ}F(4.4^{\circ} - 38^{\circ}C)$ 

## **POWER REQUIREMENTS**

Controller

Operating Voltage 24 Volt – AC

Input Supply Frequency 50 or 60 Hz

Motor Input Voltage 24 Volt – DC

Controller System

Power Consumption 3 Watts Average

Transformer

Output Voltage 24 Volt - AC 500 mA

Transformer

Input Options 115 Volt – AC 50/60 Hz

### **CYCLE INFORMATION**

Downflow/Upflow Downflow Only

Adjustable Cycles Yes

4 Cycle Valve 1) Service/Home

2) Backwash3) Slow Rinse4) Fast Rinse

#### **VALVE CONNECTIONS**

Tank Thread 2-1/2" - 8, Male

Drain Line 3/4" NPT, Female

In/Out Bypass Valve Included

Drain Line Elbow Fitting Included

In/Out Plumbing

Connection 3/4" NPT,

Male Plastic Fittings

Tank Size	DIM A	DIM B	DIM C
10x44	10-1/4 in	46 in	51 in
10x54	10-1/4 in	55-7/8 in	61-1/4 in
12x48	12 in	50 in	55-1/4 in







